

Appl. No. 09/401,694
Reply to Office Action of March 13, 2008

**RECEIVED
CENTRAL FAX CENTER**

SEP 12 2008

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (original) A system for enabling efficient utilization of available bandwidth through overlapping adjacent channels comprising:

a receiver for receiving a waveform having data information and noise information, a filter bank adapted to receive and filter said waveform and output channel information, said channel information including a combination of data signals and adjacent channel interference signals, said filter bank further adapted to provide estimated data signals and to calculate estimated interference signals; and

one or more interference generating processors adapted to receive said calculated estimated interference signals to enable said interference generating processor to generate interference signals corresponding to said calculated estimated interference signals, said interference generating processor further adapted to subtract said interference signals from said estimated data signals and to output subsequent relatively more accurate estimated data signals.

2. (original) The system of claim 1, wherein said channel information includes interfering signals from different users using the same channel, said interference generating processors being adapted to receive and calculate estimated interference from the different users of the same channel to enable said interference generating processor to generate interfering signals corresponding to the interfering users.

3. (original) The system of claim 1, comprising a decision device operable with said interference generating processors for estimating data signals in accordance with the relative ability of the information processors to cancel interference with the estimated interference signals.

Appl. No. 09/401,694

Reply to Office Action of March 13, 2008

4. (original) The system of claim 3, wherein said decision device comprises a multi-level decision device comprising a one-sided length zone of the decision device such that no decision is made in a region where the decision variable is of diminished reliability.

5. (original) The system of claim 1, comprising one or more interference estimating processors adapted to receive said relatively more accurate estimated data signals and to calculate subsequent estimated interference signals for input into said one or more interference generating processors.

6. (original) The system of claim 5, wherein said relatively more accurate estimated data signals are fed back into said one or more interference generating processors for a predetermined number of iterations.

7. (currently amended) A method for enabling efficient utilization of available bandwidth through overlapping adjacent channels, comprising:

receiving a waveform having data information and noise information;

filtering the waveform and outputting channel information through a filter bank;

producing estimated data signals corresponding to said channel information;

calculating estimated interference signals corresponding to said channel information;

[and]

generating interference signals corresponding to said calculated estimated interference signals; and

subtracting said estimated interference signals from said estimated data signals to provide relatively more accurate data signals.

8. (original) The method of claim 7, further including the step of calculating subsequent estimated interference signals from said relatively more accurate data signals.

9. (original) The method of claim 8, further including the step of feeding back said relatively more accurate data signals into said subtracting step a predetermined number of times.

123322/P/1 9/12/2008 2:20 PM

5

Appl. No. 09/401,694

Reply to Office Action of March 13, 2008

10. (original) The method of claim [8] 9, further including the step of repeating said feed back step to output increasingly accurate estimated data signals.

11. (currently amended) A system for enabling efficient utilization of available bandwidth through overlapping adjacent channels, comprising:

means for receiving a waveform having data information and noise information;

means for filtering the waveform and outputting channel information through a filter

bank;

means for producing estimated data signals corresponding to said channel information;

means for calculating estimated interference signals corresponding to said channel

information;[and]

means for generating interference signals corresponding to said calculated estimated interference signals; and

means for subtracting said estimated interference signals from said estimated data signals to provide relatively more accurate data signals.

12. (original) The system of claim 11, further including means for calculating subsequent estimated interference signals from said relatively more accurate data signals.

13. (original) The system of claim 12, further including means for feeding back said relatively more accurate data signals into said subtracting step a predetermined number of times.

14. (currently amended) The system of claim [12]13, further including means for repeating said feed back step to output increasingly accurate estimated data signals.